



Application Guide for Profile® Engineered Fiber Matrix™

Application / Loading Procedures

- A. Strictly comply with equipment Manufacturer's installation instructions and recommendations. Use approved hydro-spraying machines with fan-type nozzle (50-degree tip) whenever possible to achieve best soil coverage. Apply from opposing directions to assure 100% soil surface coverage. Slope interruption devices or water diversion techniques are recommended when slope lengths exceed the maximum recommendations as shown in the Slope Application and Slope Interruption Limits tables on the back page of these guidelines.
- B. To ensure proper application rates, measure and stake area. For maximum performance, apply EFM as follows:
 1. Apply fertilizer with specified prescriptive agronomic formulations, seed and EFM at a rate of 60 pounds per 100 gallons (27 kg/379 liters) of water over properly prepared surfaces.
 2. See loading chart on the back and confirm loading rates with equipment manufacturer. Do not leave seeded surfaces unprotected, especially if precipitation is imminent.
- C. Fill 1/3 of mechanically agitated hydroseeder with water. Turn pump on for 15 seconds and purge and pre-wet lines. Turn pump off.
- D. Turn agitator on and load low density materials first (i.e. seed).**
- E. Continue slowly filling tank with water while loading fiber matrix into tank.
- F. Consult loading chart on the back to determine the number of bags to be added for desired area and application rate.
- G. EFM should be completely loaded before water level reaches 75% of the top of tank.
- H. Add fertilizer as water level approaches the top of the tank.
- I. Top off with water and mix until all fiber is fully broken apart and hydrated (minimum of 10 minutes — increase mixing time when applying in cold conditions). This is very important to fully activate the bonding additives and to obtain proper viscosity.
- J. Shut off recirculation valve to minimize potential for air entrainment within the slurry.
- K. Slow down agitator and start applying with a 50-degree fan tip nozzle.
- L. Spray in opposing directions for maximum soil coverage.

**Best results and more rapid curing are achieved at temperatures exceeding 60°F (15°C). Curing times may be accelerated in high temperature, low humidity, and windy conditions with product applied on dry soils.*

***Do not add additional tackifiers or polymers to this pre-mixed formulation.*

Loading Chart for Profile's Engineered Fiber Matrix

Tank Size (gal)	# of 50-lb bales	(lb)	Displacement (gal)	2,500 lb/acre		3,000 lb/acre		3,500 lb/acre		4,000 lb/acre	
				Sq ft	Acres	Sq ft	Acres	Sq ft	Acres	Sq ft	Acres
250	3	150	280	2,614	0.060	2,178	0.050	1,867	0.043	1,634	0.038
500	6	300	560	5,227	0.120	4,356	0.100	3,734	0.086	3,267	0.075
750	9	450	840	7,841	0.180	6,534	0.150	5,601	0.129	4,901	0.113
1,000	12	600	1,120	10,454	0.240	8,712	0.200	7,467	0.171	6,534	0.150
1,500	18	900	1,680	15,682	0.360	13,068	0.300	11,201	0.257	9,801	0.225
2,000	24	1,200	2,240	20,909	0.480	17,424	0.400	14,935	0.343	13,068	0.300
2,500	30	1,500	2,800	26,136	0.600	21,780	0.500	18,669	0.429	16,335	0.375
3,000	36	1,800	3,360	31,363	0.720	26,136	0.600	22,402	0.514	19,602	0.450
3,500	42	2,100	3,920	36,590	0.840	30,492	0.700	26,136	0.600	22,869	0.525
4,000	48	2,400	4,480	41,818	0.960	34,848	0.800	29,870	0.686	26,136	0.600

Additional Notes:

- Rough surfaces (rocky terrain, cat tracks, ripped soils, etc.) may require additional product to achieve 100% coverage.
 - Be sure to allow for residual material in tank on subsequent applications.

Application Rates		
Slope Condition	English	SI
< 4H to 1V	2500 lb/acre	2800 kg/hectare
> 4H to 1V and < 3H to 1V	3000 lb/acre	3400 kg/hectare
> 3H to 1V and < 2H to 1V	3500 lb/acre	3900 kg/hectare
> 2H to 1V and < 1H to 1V ¹	4000 lb/acre	4500 kg/hectare
Slope Interruption Limits*		
Product Category	Length (ft)	Length (m)
EFM	50	15

For conversions:

1 kg = 0.454 lb

1 ha = 0.41 ac

0.45 kg/0.4 ha = 1.12 x lb/ac

¹EFM not recommended for slopes greater than 1H:1V.

*Listed slope interruption limits are for product applications on a 3H:1V slope. For application on steeper slopes, slope interruption lengths may need to be decreased.

Visual Key for Proper Application

Proper Application

Improper Application



3,000 lb/acre



3,500 lb/acre



4,000 lb/acre



} 3.4 mm thickness

} 4.0 mm thickness

} 4.6 mm thickness



Solutions for your Environment™

PROFILE Products LLC
750 Lake Cook Road, Suite 440
Buffalo Grove, IL 60089
(800) 508-8681
www.profileproducts.com



U.S. Patent #'s: 5,741,832; 5,779,782; 5,942,029; 6,158,167; 6,360,478; 7,752,804 and Patents Pending