

Corporate Office
1329 N. Riverfront Dr.
Mankato, MN 56001
Phone (507) 387-4091
Fax: (507) 387-7033



Sales Office
731 N. Prior Ave
Saint Paul, MN 55104
Phone: (651) 917-0939
Fax: (651) 917-0111

HYPER-TACK - ANIONIC POLYACRYLAMIDE

PRODUCT DESCRIPTION:

Hyper-Tack is a premium polyacrylamide designed for hydromulching, hydroseeding, and dust control applications.

Hyper-Tack increases soil porosity and reduces sediment runoff through soil agglomeration and flocculating suspended sediment.

Hyper-Tack provides optimal slurry viscosity for ease of application.

Hyper-Tack provides for temporary erosion control during vegetative establishment.

SPECIFICATIONS:

Active Ingredient: Linear Co-Polymer of acrylamide and sodium acrylate

Minimum Active Ingredient: 90%

Ionic Charge: Anionic

Molecular Weight: 16,000-20,000

Environmental Certifications: ANSI/NSF Standard 60, contains less than 0.05% residual acrylamide.

APPLICATION RATE:

For temporary erosion control, it is recommended that Hyper-Tack be applied at 6 to 8 lbs per 1000 gallons of water. The use of mulch at a rate of 150 to 300 lbs may be added as a marker.

SLOPE FLAT	3:1	2:1	1:1	
LB/ACRE	3-5	5-10	10-20	20-30

PACKAGING

25 lb Bucket

ti