



# Terra-Mulch® Terra-Blend™ with Tacking Agent 3®

## Wood/Cellulose Blend with Tackifier

Enhances fiber-to-soil bond

- Terra-Blend™ combines Thermally Refined® wood fiber with a high quality of cellulose pre-blended with Tacking Agent 3®
- Tacking Agent 3 is a three-dimensional blend of polymers and guar gum, proven to reduce soil erosion and water runoff immediately after hydroseeding—no cure time required
- Enhanced water-holding capacity due to refined wood fibers, allowing for better germination, fewer washouts and reduced callbacks
- Flexibility of blend fiber combined with tackifier allows equipment to run efficiently and for more extensive hose work without clogs
- Non-toxic and environmentally safe
- Meets or exceeds all requirements for wood fiber mulch
- Maximum slope length of 25 feet
- Use approved hydroseeding equipment for optimum pumping and application performance
- Terra-Blend with Tacking Agent 3 functional longevity is  $\leq 3$  months



### Product Composition:

Thermally Refined® Wood Fibers (minimum) – 58%  $\pm$  3%

Cellulose Fiber (maximum) – 27%  $\pm$  3%

Tacking Agent 3® – 3%  $\pm$  1%

Moisture Content – 12%  $\pm$  3%

(40) 50-lb bales per pallet

#### Slope Gradient/Condition

$\leq 4\text{H}:1\text{V}$

$> 4\text{H}:1\text{V}$  and  $\leq 3\text{H}:1\text{V}$

#### Rate

2000 lb/acre

2500 lb/acre



PROFILE Products LLC · 750 Lake Cook Road · Suite 440 · Buffalo Grove, IL 60089

Technical Assistance: 800-508-8681

[www.profileproducts.com](http://www.profileproducts.com)