



Terra-Mulch® Terra-Wood™ with Tacking Agent 3®

Wood Fiber with Tackifier

Enhanced water-holding capacity excels growth

- 100% wood fiber is just like Terra-Wood,™ but with the industry's leading tackifier, Tacking Agent 3®
- Tacking Agent 3 is a three-dimensional blend of polymers and guar gum, proven to reduce soil erosion and water runoff immediately after hydroseeding—no cure time required
- Controls erosion without having to cure—ideal on critical sites with up to 2H:1V slopes
- Wood fibers interlock for a more secure fiber-to-soil bond
- Contractors report that our wood fiber delivers up to 30% more yield than competitive products, which means more money in their pockets
- Non-toxic and environmentally safe
- Meets or exceeds all requirements for wood fiber mulch
- Maximum slope length of 30 feet
- Use approved hydroseeding equipment for optimum pumping and application performance
- Terra-Wood with Tacking Agent 3 functional longevity is ≤ 3 months



Product Composition:

Thermally Refined® Wood Fibers – 85% \pm 3%

Tacking Agent 3® – 3% \pm 1%

Moisture Content – 12% \pm 3%

(40) 50-lb bales per pallet

Slope Gradient/Condition

$\leq 4H:1V$ 2000 lb/acre

$> 4H:1V$ and $\leq 3H:1V$ 2500 lb/acre

$> 3H:1V$ and $\leq 2H:1V$ 3000 lb/acre

Rate



PROFILE Products LLC · 750 Lake Cook Road · Suite 440 · Buffalo Grove, IL 60089

Technical Assistance: 800-508-8681

www.profileproducts.com