



Terra-Mulch® Terra-Blend™ with UltraGro™ Wood/Cellulose Fiber

Now with TriFlo! — makes the best hydraulic mulch even better!

- Improves moisture retention
- Improves the suspension of mulch, seed and fertilizer within the slurry and prevents the dewatering of the fiber mulch
- Improves the application of hydraulic mulch in a more uniform layer for better coverage and enhanced product performance
- Improves application efficiency by increasing shooting distance and enhancing hose performance—greatly reducing downtime associated with clogging



The ultimate in blend performance!

- Terra-Blend™ with UltraGro™ combines 100% Thermally Refined® wood fiber with the highest quality cellulose fibers
- Now combined with UltraGro, a proprietary biostimulant, to ensure healthy growth even in harsh environments
- Delivers up to 15% greater yield to contractors when compared to competitive blend products
- Provides superior erosion control and more complete germination
- Covers up to 20% more ground than cellulose without an increase in price
- Non-toxic and environmentally safe
- Meets or exceeds all requirements for wood fiber mulch
- Maximum slope length of 23 feet
- Use approved hydroseeding equipment for optimum pumping and application performance
- Terra-Blend with UltraGro functional longevity is ≤ 3 months



Product Composition:

Thermally Refined® Wood Fibers (minimum) – 60%
Cellulose Fiber (maximum) – 27%
Moisture Content – 12% \pm 3%
Natural Biostimulant – 1% \pm 0.5%
(40) 50-lb bales per pallet

Slope Gradient/Condition
 $\leq 4H:1V$
 $> 4H:1V$ and $\leq 3H:1V$

Rate
2000 lb/acre
2500 lb/acre

